

GLAND EYE BOLT DIN 444



Type A (product grade C = design g)
 Type B (product grade B = design m)
 Type C (product grade A = design m)

W HREAD D1		M5	M6	M8	M10	M12	M16	M20	M24	(M27)	M30	(M33)	M36	(M39)		
P		0.8	1	1.25	1.5	1.75	2	2.5	3	3	3.5	3.5	4	4		
b (+2P - 0)	l<=125	16	18	22	26	30	38	46	54	60	66	/	/	/		
	125<l<=200	/	/	28	32	36	44	52	60	66	72	78	84	90		
	l>200	/	/	/	/	49	57	65	73	79	85	91	97	103		
d2 H9		5	6	8	10	12	16	18	22	24 25	27 28	30	32 33	35 36		
d3	max.		12	14	18	20	25	32	40	45	50	55	60	65	70	
	min.	Type A	10.9	12.9	16.9	18.7	23.7	30.4	38.4	43.4	48.4	53.1	58.1	63.1	68.1	
	Type B and C		11.57	13.57	17.57	19.48	24.48	31.38	39.38	44.38	49.38	54.26	59.26	64.26	69.26	
r ≈		2.5	4	4	4	6	6	6	10	10	10	16	16	16		
s	Type A	max.		8	9	11	14	17	19	24	28	30	34	38	41	46
	min.		7.52	8.52	10.3	13.3	16.3	18.16	23.16	27.16	29.16	33	37	40	45	
s	Type B and C	max.		6	7	9	12	14	17	22	25	27	30	34	38	41
	min.		5.88	6.85	8.85	11.82	13.82	16.82	21.79	24.79	26.79	29.79	33.75	37.75	40.75	

* All dimensions are in mm.

*All the data are from informative purpose only

